

# FIOS DE NYLON

## FIO ENTRANÇADO DE NYLON



REFERÊNCIA	TIPO	DIÂMETRO mm	MTS Kg	CARGA DE ROTURA Kg
DIVFENY010	8841	1,0	800	50
DIVFENY015	8842	1,5	600	78
DIVFENY020	8843	2,0	400	100
DIVFENY025	4840/3	2,5	280	140
DIVFENY030	4840/4	3,0	180	200
DIVFENY040	4840/4.1/2	4,0	130	280
DIVFENY050	4840/5	5,0	110	370
DIVFENY060	4840/6	6,0	75	460
DIVFENY080	4840/8	8,0	50	550

## FIO TORCIDO DE NYLON



REFERÊNCIA	TIPO	N.º DE CABOS	RESISTÊNCIA Kg	MTS Kg	QUANTIDADE POR BOBINE Kg
DIVMUL21004_	210/4	3	5,600	9.280	0,250 / 0,500
DIVMUL21006_	210/6	3	7,600	6.750	0,250 / 0,500
DIVMUL21009_	210/9	3	10,200	4.400	0,250 / 0,500
DIVMUL21012_	210/12	3	14,900	3.200	0,250 / 0,500
DIVMUL21015_	210/15	3	19,200	2.650	0,250 / 0,500
DIVMUL21018_	210/18	3	24,600	2.200	0,250 / 0,500
DIVMUL21021_	210/21	3	28,000	1.800	0,250 / 0,500
DIVMUL21024_	210/24	3	32,000	1.600	0,250 / 0,500
DIVMUL21027_	210/27	3	34,000	1.400	0,250 / 0,500
DIVMUL21030_	210/30	3	37,000	1.200	0,250 / 0,500
DIVMUL21036_	210/36	3	40,000	1.050	0,250 / 0,500
DIVMUL21042_	210/42	3	44,000	875	0,250 / 0,500
DIVMUL21045_	210/45	3	48,000	800	0,250 / 0,500
DIVMUL21048_	210/48	3	53,900	775	0,250 / 0,500
DIVMUL21060_	210/60	3	73,800	530	0,250 / 0,500
DIVMUL21072_	210/72	3	93,700	450	0,250 / 0,500
DIVMUL21096_	210/96	3	110,000	310	0,250 / 0,500

Cores disponíveis: Branco - Castanho - Preto

No final da referência indicar:

Branco	B1 - 250g	B2 - 500g
Castanho	C1 - 250g	C2 - 500g
Preto	P1 - 250g	P2 - 500g

